

Network Working Group  
Request for Comments: 1782  
Updates: 1350  
Category: Standards Track

G. Malkin  
Xylogics, Inc.  
A. Harkin  
Hewlett Packard Co.  
March 1995

## TFTP Option Extension

### Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

### Abstract

The Trivial File Transfer Protocol [1] is a simple, lock-step, file transfer protocol which allows a client to get or put a file onto a remote host. This document describes a simple extension to TFTP to allow option negotiation prior to the file transfer.

### Introduction

The option negotiation mechanism proposed in this document is a backward-compatible extension to the TFTP protocol. It allows file transfer options to be negotiated prior to the transfer using a mechanism which is consistent with TFTP's Request Packet format. The mechanism is kept simple by enforcing a request-respond-acknowledge sequence, similar to the lock-step approach taken by TFTP itself.

While the option negotiation mechanism is general purpose, in that many types of options may be negotiated, it was created to support the Blocksize option defined in [2]. Additional options are defined in [3].


This document assumes reader familiarity with the TFTP specification [1] and its terminology.

### Packet Formats

TFTP options are appended to the Read Request and Write Request packets. A new type of TFTP packet, the Option Acknowledgment (OACK), is used to acknowledge a client's option negotiation request. A new error code, 8, is hereby defined to indicate that a transfer should be terminated due to option negotiation.



The OACK packet has the following format:



opc

The opcode field contains a 6, for Option Acknowledgment.

opt1

The first option acknowledgment, copied from the original request.

value1

The acknowledged value associated with the first option. If and how this value may differ from the original request is detailed in the specification for the option.

optN, valueN

The final option/value acknowledgment pair.

### Negotiation Protocol

The client appends options at the end of the Read Request or Write request packet, as shown above. Any number of options may be specified; however, an option may only be specified once. The order of the options is not significant.

If the server supports option negotiation, and it recognizes one or more of the options specified in the request packet, the server may respond with an Options Acknowledgment (OACK). Each option the server recognizes, and accepts the value for, is included in the OACK. Some options may allow alternate values to be proposed, but this is an option specific feature. The server must not include in the OACK any option which had not been specifically requested by the client; that is, only the client may initiate option negotiation. Options which the server does not support should be omitted from the OACK; they must not cause an ERROR packet to be generated. If the value of a supported option is invalid, the specification for that option will indicate whether the server should simply omit the option from the OACK, respond with an alternate value, or send an ERROR packet, with error code 8, to terminate the transfer.

An option not acknowledged by the server must be ignored by the client and server as if it were never requested. If multiple options were requested, the client must use those options which were acknowledged by the server and must not use those options which were not acknowledged by the server.

When the client appends options to the end of a Read Request packet, three possible responses may be returned by the server:

- OACK - acknowledge of Read Request and the options;
- DATA - acknowledge of Read Request, but not the options;
- ERROR - the request has been denied.

When the client appends options to the end of a Write Request packet, three possible responses may be returned by the server:

- OACK - acknowledge of Write Request and the options;
- ACK - acknowledge of Write Request, but not the options;
- ERROR - the request has been denied.

If a server implementation does not support option negotiation, it will likely ignore any options appended to the client's request. In this case, the server will return a DATA packet for a Read Request and an ACK packet for a Write Request establishing normal TFTP data transfer. In the event that a server returns an error for a request which carries an option, the client may attempt to repeat the request without appending any options. This implementation option would handle servers which consider extraneous data in the request packet to be erroneous.

Depending on the original transfer request there are two ways for a client to confirm acceptance of a server's OACK. If the transfer was initiated with a Read Request, then an ACK (with the data block number set to 0) is sent by the client to confirm the values in the server's OACK packet. If the transfer was initiated with a Write Request, then the client begins the transfer with the first DATA packet, using the negotiated values. If the client rejects the OACK, then it sends an ERROR packet, with error code 8, to the server and the transfer is terminated.

Once a client acknowledges an OACK, with an appropriate non-error response, that client has agreed to use only the options and values returned by the server. Remember that the server cannot request an option; it can only respond to them. If the client receives an OACK containing an unrequested option, it should respond with an ERROR packet, with error code 8, and terminate the transfer.

## Examples

## Read Request

client	server
1 foofile 0 octet 0 blksize 0 1432 0  -->	RRQ
	<--  6 blksize 0 1432 0  OACK
4 0  -->	ACK
4 1  -->	<--  3 1  1432 octets of data   DATA
4 2  -->	ACK
	<--  3 2  1432 octets of data   DATA
4 2  -->	ACK
	<--  3 3 <1432 octets of data   DATA
4 3  -->	ACK

## Write Request

client	server
2 barfile 0 octet 0 blksize 0 2048 0  -->	RRQ
	<--  6 blksize 0 2048 0  OACK
3 1  2048 octets of data   -->	DATA
	<--  4 1  ACK
3 2  2048 octets of data   -->	DATA
	<--  4 2  ACK
3 3 <2048 octets of data   -->	DATA
	<--  4 3  ACK

## Security Considerations

Security issues are not discussed in this memo.

## References

- [1] Sollins, K., "The TFTP Protocol (Revision 2)", STD 33, RFC 1350, MIT, July 1992.
- [2] Malkin, G., and A. Harkin, "TFTP Blocksize Option", RFC 1783, Xylogics, Inc., Hewlett Packard Co., March 1995.
- [3] Malkin, G., and A. Harkin, A., "TFTP Timeout Interval and Transfer Size Options", RFC 1784, Xylogics, Inc., Hewlett Packard Co., March 1995.

## Authors' Addresses

Gary Scott Malkin  
Xylogics, Inc.  
53 Third Avenue  
Burlington, MA 01803

Phone: (617) 272-8140  
EMail: gmalkin@xylogics.com

Art Harkin  
Internet Services Project  
Information Networks Division  
19420 Homestead Road MS 43LN  
Cupertino, CA 95014

Phone: (408) 447-3755  
EMail: ash@cup.hp.com